



YASKAWA

DECLARATION OF CONFORMITY

Ref.No.P99044

Nov.22, 1999

Jul.31, 2001

We declare under our sole responsibility that the product
Inverter series VS mini J7 as listed below

CIMR-J7□□□ 0 P 1 1 2 3	CIMR-J7□□□ 0 P 2 1 2 3	CIMR-J7□□□ 0 P 4 1 2 3
CIMR-J7□□□ 0 P 7 1 2 3	CIMR-J7□□□ 1 P 5 1 2 3	CIMR-J7□□□ 2 P 2 1 2 3
CIMR-J7□□□ 3 P 7 1 2 3	CIMR-J7□□□ 4 P 0 1 2 3	CIMR-J7□□□ 4 3 P 0 1 2


1. Model A/R - With digital operator (with potentiometer)
B/S - Without digital operator (with blank cover)
C/T - With digital operator (without potentiometer)
(R,S, and T are flat_heatsink version)
2. Specifications A - Japanese Version
U - American Version
C - European Version
D to Z - OEM Version (excluding "U")
3. Voltage class 2 - Three - Phase, 200V
B - Single - Phase, 200V (Model Type B0P1~B1P5)
4 - Three - Phase, 400V

to which this declaration relates is in conformity with the following standard .

EN50178 1997

following the provisions of Low Voltage Directive 73/23/EEC, as amended by 93/68/EEC.

YASKAWA ELECTRIC CORPORATION
 INVERTER PLANT
 2-13-1 Nishimiyaichi, Yukuhashi City
 Fukuoka Pref, 824 Japan
 Jul.31, 2001


 Kazuhisa Akieda
 General Manager
 Inverter Plant

DECLARATION OF CONFORMITY



YASKAWA

Ref.No.P02082

Dec.24, 2002

We declare under our sole responsibility that the product

Inverter series VS mini J7 as listed below

CIMR-J7
1 2 3 4 5

1 - Model

J7: VS mini J7 series

2 - Type

A /R: With digital operator (with volume)
B /S: Without digital operator (with blank cover)
C /T: With digital operator (without volume)
(R,S, and T are flat heatsink version)

3 - Specifications

A: Japanese standard model C: European standard model U: American standard model
D to Z: OEM Version (excluding "U")

4 - Voltage class

2: Three phase 200V (Model Type 20P1 - 24P0; excluding 23P0)
4: Three phase 400V (Model Type 40P2 - 44P0)
B: Single phase 200V (Model Type B0P1 - B1P5)

5 - Maximum applicable motor capacity

0P1: 0.1kW 0P2: 0.2kW 0P4: 0.4kW 0P7: 0.75kW 1P5: 1.5kW 2P2: 2.2kW
3P0: 3.0kW 3P7: 3.7kW 4P0: 4.0kW

To which this declaration relates is in conformity with the following standard

The limits and requirements according to product standard
EN61800-3 dd.1996 and EN61800-3+A11 dd.2000-01

Conducted RF emissions (AC mains port)	EN55022(1994) Class B
Radiated RF emissions (Enclosure)	EN55022(1994) Class B
Electrostatic discharge 6kV contact, 8kV Air	EN61000-4-2(1995)
Fast transient common mode	EN61000-4-4(1995)
4kV a.c power input port, 2kV a.c motor output port, 1kV control port	
Slow transients (Surge)	EN61000-4-5,1995-03
Conducted RF immunity 10Vrms	EN61000-4-6(1996)
Radiated RF immunity (Enclosure) 10V/m	EN61000-4-3(1996)
Radiated RF immunity (Pulse modulated) 10V/m	ENV50204(1995)
Magnetic Field immunity 30A/m	EN61000-4-8(1994)

following the provisions of EMC Directive 89/336/EEC
amended by 91/263/EEC,92/31/EEC,93/68/EEC

YASKAWA ELECTRIC CORPORATION
2-13-1 Nishimiyaichi Yukuhashi City
Fukuoka Pref, 824-8511 Japan
Dec.24, 2002

Tatsumi TSURUTA
General Manager
Drive Business Sector
Motion Control Division