



The recommended bend radius is 15mm or larger.

MOTOR END CONNECTOR

Item		Description		
Order Number		JZSP-C7M9-1-E		
Manufacturer		J.S.T. Mfg. Co., Ltd.		
User Instructions		JFA Connector J-1700		
Compo- Receptac		J17S-06FMH-7KL-M-CF		
nents	Contacts	SJ1F-01GF-P0.8		
Applicable Wire Sizes		Power terminals: AWG20 Holding brake terminals: AWG20 to AWG24		
Applicable Cable Diameter		7 mm ±0.3 mm		
Outer Diameter of Insulating Sheath		1.11 mm to 1.53 mm		
Mounting Screws		M2 pan-head screws		
Crimp-	Hand Tool	YRS-8841		
ing Tool*	Applicator	APLMK SJ1F/M01-08		
External Dimensions [mm]		Ecable on Load Side 25.8 Pin 1 Pin 6 Pin 1 Pin 6 Pin 1 Pin 6		

RAW CABLE

Item	Standard Cable
Order Number*	JZSP-CSM90-□□-E (maximum length: 50 m)
	UL2517 (rated temperature:105°C) AWG20 × 6C
Specifications	Power lines: AWG20 (0.52 mm²) Outer diameter of insulating sheath: 1.53 mm
	Holding brake lines: AWG20 (0.52 mm²) Outer diameter of insulating sheath: 1.53 mm
Finished Diameter	7 mm ±0.3 mm
Internal Structure and Lead Colors	Green Black White White Black Black

^{*} Replace the boxes ($\square\square$) in the order number with the cable length (05, 10, 15, 20, 30, 40, or 50).

WIRING SPECIFICATIONS

SERVOPACK Leads			Servomotor	ervomotor Connector	
	Wire Color	Signal	Signal	Pin	
	Green/yellow	FG	FG	1	
	Blue	Phase W	Phase W	2	
	White	Phase V	Phase V	3	
	Red	Phase U	Phase U	4	
	Black	Brake	Brake	5	
	Black	Brake	Brake	6	

Note: There is no polarity for the connection to the holding brake.

ITEM NUMBER	L=Length	
JZSP-C7M13F-03-E	3000	
JZSP-C7M13F-05-E	5000	
JZSP-C7M13F-10-E	10000	
JZSP-C7M13F-15-E	15000	
JZSP-C7M13F-20-E	20000	
JZSP-C7M13F-30-E	30000	
JZSP-C7M13F-40-E	40000	
JZSP-C7M13F-50-E	50000	

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE PUBLIC AND CAN BE DISCLOSED WITHOUT EXPRESS WRITTEN CONSENT OF YASKAWA AMERICA INC. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE FOR ONGOING PRODUCT MODIFICATIONS AND IMPROVEMENTS.

YASKAWA

ITLE:SGM7J/7A -A5 to -C2. 50W to 150W Servomotor Power Cable, Brake, Toward Load, Non-Flex, Non-Shielded

TEM #:

JZSP-C7M13F-xx-E (xx = See Chart)

SIZE REVISION PAGE
- 0 1 of 1

SCALE: NTS UNITS: mm

mm SHEET: 1/1

DRAWING #:
1 CAD-JZSP-C7M13F-xx-E

 \ast A Crimping Tool is required. Contact the connector manufacturer for details.

REV	DESCRIPTION	DATE	DRAWN BY
0	Initial Release	12/20/2018	E. SONDERMAN