


YASKAWA




SCALE 1:2

TITLE
HV305 DIMENSION DRAWING
FRAME SIZE 1.2
IP20 ENCLOSURE


SIZE	A	PAGE	1 OF 3
DWG.NO.			
DD.HV305.FR1.2.IP20			

REV
0

FRONT VIEW



BOTTOM VIEW



C/C: HV35□	TERMINAL SYMBOL	WIRE RANGE AWG (mm²)	TERMINAL SCREW	CLAMPING TORQUE N.m. (lb.in.)
2004□□□	R/L1, S/L2, T/L3	14 - 12 (2.5 - 4)	M3	0.6 - 0.8 (5 - 7)
	U/T1, V/T2, W/T3	14 - 12 (2.5 - 4)	M3	0.6 - 0.8 (5 - 7)
	-, +1, +2	14 - 12 (2.5 - 4)	M3	0.6 - 0.8 (5 - 7)
	B1, B2	14 - 12 (2.5 - 4)	M3	0.6 - 0.8 (5 - 7)
	⊕	14 (2.5)	M3.5	0.8 - 1.0 (7 - 9)

□ Denotes A-Z
Note: Refer to applicable codes and standards for proper wire type and size.

YASKAWA

UNITS MM [IN]
SCALE 1:2

DRWN.	J. MATTAS	9-20-22
CHKD.	J. PIOTROWSKI	9-21-22
TECH.	L. UDDIN	9-27-22
APRV.	J. CAIRO	9-27-22


TITLE
HV305 DIMENSION DRAWING
FRAME SIZE 1.2
IP20 ENCLOSURE

SIZE A
PAGE 2 OF 3
DWG.NO.
DD.HV305.FR1.2.IP20

REV
0

Minimum Installation Clearances


Scale 1:3



Note:
For alternate mounting configurations, consult manual.

Panel Cutout For External Heatsink Mounting Configuration

Scale 1:2



Notes:
Exposed heatsink minimum clearance = 43.5 [1.71].
Refer to external heatsink instructions document for additional details.

YASKAWA



UNITS MM [IN]

SCALE ABOVE

DRWN.	J. MATTAS	9-20-22
CHKD.	J. PIOTROWSKI	9-21-22
TECH.	L. UDDIN	9-27-22
APRV.	J. CAIRO	9-27-22

TITLE
HV305 DIMENSION DRAWING
FRAME SIZE 1.2
IP20 ENCLOSURE

SIZE	A
PAGE	3 OF 3
DWG.NO.	DD.HV305.FR1.2.IP20

REV
0