

A.C. INPUT		
Volts:		Hz:
Phase:		Amps:
[SCCR:]		
A.C. OUTPUT		
Volts:		Hz:
Phase:		Amps:
[]		
Designator	Rating	Type
[F1, F2]		
[F6]		
[EZ]		
[F3, F4, F5]		
[F8, F9, F10]		
Serial No.:		
Model No.:		
Type.:		
W.D.:		
Inst. Manual.:		

SUMMARY OF PAGES		
PRODUCT	SCCR	INFO
P1C1	PAGES 2 AND 3	
P1C2	PAGES 4 AND 5	
P1C3	PAGES 6 AND 7	

FIGURE 1

SCCR: ① kA rms sym., ② V max.

USE FORMAT: UNPN0083-SCCR 1

SCCR: ① kA rms sym., ② V max.,
with ③ A max., Class ④ fuses

USE FORMAT: UNPN0083-SCCR 2

SCCR: ① kA rms sym., ② V max.,
with ③ NTD fuses

USE FORMAT: UNPN0083-SCCR 3


SCCR: ① kA rms sym., ② V max.,
or
③ kA rms sym., ② V max.,
with ④ A max., Class ⑤ fuses

USE FORMAT: UNPN0083-SCCR 4

SCCR: ① kA rms sym., ② V max.,
with ③ kAIR min., ④ A fuses or MCCB

USE FORMAT: UNPN0083-SCCR 5

REVISIONS				
REV.	DESCRIPTION	ECO #	DRAWN BY	DATE
02	ADDED NEW TYPE 3R DATA	3615	KM	8/23/12
01	REPLACE SQ. D D FRAME CB/MCS'S W/ L FRAME	3470	KM	6/5/12
00	INITIAL RELEASE	-	KM	3/19/12

	DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
	CHECKED: D.R. CMELAK	DATE: 8/23/12			
	TECH:	DATE:			
	APPROVED: K. FLIERL	DATE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 1 of 7
ORIGINAL DESIGN: D.R. CMELAK		DATE: 3/19/12	DRAWING #: UDA00744		

THIS DOCUMENT AND INFORMATION
CONTAINED IN IT ARE CONFIDENTIAL,
AND CANNOT BE COPIED OR
DISCLOSED IN WHOLE OR IN PART
WITHOUT THE EXPRESS WRITTEN
CONSENT OF YASKAWA AMERICA INC.

TABLE 1

		WITHOUT OPTIONS PC,PD OR PE		WITH OPTION PC		WITH OPTION PE		WITH OPTION PD	
WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083- SCCR_	①	②	①	②	①	②	①	②
P1C1A002	1	10	240	65	240	25	240	5	240
P1C1A003	1	10	240	65	240	25	240	5	240
P1C1A004	1	10	240	65	240	25	240	5	240
P1C1A006	1	10	240	65	240	25	240	5	240
P1C1A009	1	10	240	65	240	25	240	5	240
P1C1A015	1	10	240	65	240	25	240	5	240
P1C1A022	1	10	240	65	240	25	240	5	240
P1C1A028	1	10	240	65	240	25	240	5	240
P1C1A042	1	10	240	65	240	25	240	5	240
P1C1A054	1	10	240	65	240	25	240	5	240
P1C1A068	1	10	240	65	240	25	240	5	240
P1C1A080	1	10	240	65	240	25	240	5	240
P1C1A104	1	10	240	65	240	25	240	5	240
P1C1A130	1	10	240	65	240	25	240	5	240
P1C1A154	1	10	240	65	240	25	240	5	240
P1C1A192	1	10	240	65	240	65	240	SEE TABLE 2	
P1C1A248	1	10	240	65	240	65	240		
P1C1A312	1	10	240	65	240	65	240		
P1C1A360	1	10	240	65	240	65	240		
P1C1B001	1	10	480	65	480	18	480	5	480
P1C1B002	1	10	480	65	480	18	480	5	480
P1C1B003	1	10	480	65	480	18	480	5	480
P1C1B004	1	10	480	65	480	18	480	5	480
P1C1B007	1	10	480	65	480	18	480	5	480
P1C1B011	1	10	480	65	480	18	480	5	480
P1C1B014	1	10	480	65	480	18	480	5	480
P1C1B021	1	10	480	65	480	18	480	5	480
P1C1B027	1	10	480	65	480	18	480	5	480
P1C1B034	1	10	480	65	480	18	480	5	480
P1C1B040	1	10	480	65	480	18	480	5	480
P1C1B052	1	10	480	65	480	18	480	5	480
P1C1B065	1	10	480	65	480	18	480	5	480
P1C1B077	1	10	480	65	480	18	480	5	480
P1C1B096	1	10	480	65	480	18	480	5	480
P1C1B124	1	10	480	65	480	18	480	5	480
P1C1B156	1	10	480	65	480	18	480	5	480
P1C1B180	1	10	480	65	480	35	480	SEE TABLE 2	
P1C1B240	1	10	480	65	480	35	480		
P1C1B302	1	10	480	65	480	35	480		
P1C1B361	1	10	480	65	480	35	480		
P1C1B414	1	10	480	65	480	35	480		
P1C1B477	1	10	480	65	480	35	480		
P1C1B515	1	10	480	65	480	35	480		
P1C1B590	1	10	480	65	480	35	480		
P1C1B660	1	10	480	65	480	35	480		
P1C1B720	1	10	480	65	480	35	480		
P1C1B810	1	10	480	65	480	35	480		
P1C1B900	1	10	480	65	480	35	480		
P1C1B930	1	10	480	65	480	35	480		
P1C1BK09	1	10	480	65	480	35	480		
P1C1BK20	1	10	480	65	480	35	480		

TABLE 2

		WITH OPTION PD			
WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083- SCCR_	①	②	③	④
P1C1A192	5	65	240	65	250
P1C1A248	5	65	240	65	400
P1C1A312	5	65	240	65	400
P1C1A360	5	65	240	65	600
P1C1B180	5	35	480	35	250
P1C1B240	5	35	480	35	400
P1C1B302	5	35	480	35	400
P1C1B361	5	35	480	35	400
P1C1B414	5	35	480	35	600
P1C1B477	5	65	480	65	600
P1C1B515	5	65	480	65	600
P1C1B590	5	65	480	65	800
P1C1B660	5	65	480	65	800
P1C1B720	5	65	480	65	1200
P1C1B810	5	65	480	65	1200
P1C1B900	5	65	480	65	1200
P1C1B930	5	65	480	65	1200
P1C1BK09	5	65	480	65	1200
P1C1BK20	5	65	480	65	1600

YASKAWA
 THIS DOCUMENT AND INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF YASKAWA AMERICA INC.

DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
CHECKED: D.R. CMELAK	DATE: 8/23/12			
TECH:	DATE:			
APPROVED: K. FLIERL	DATE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 2 of 7
ORIGINAL DESIGN: D.R. CMELAK	DATE: 3/19/12	DRAWING #: UDA00744		

TABLE 3

WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083-SCCR_	WITHOUT OPTIONS PC,PD OR PE		WITH OPTION PC		WITH OPTION PE		WITH OPTION PD	
		①	②	①	②	①	②	①	②
P1C1C1P3	1	10	600	50	600	14	600	5	600
P1C1C1P7	1	10	600	50	600	14	600	5	600
P1C1C002	1	10	600	50	600	14	600	5	600
P1C1C003	1	10	600	50	600	14	600	5	600
P1C1C006	1	10	600	50	600	14	600	5	600
P1C1C009	1	10	600	50	600	14	600	5	600
P1C1C011	1	10	600	50	600	14	600	5	600
P1C1C017	1	10	600	50	600	14	600	5	600
P1C1C022	1	10	600	50	600	14	600	5	600
P1C1C027	1	10	600	50	600	14	600	5	600
P1C1C032	1	10	600	50	600	14	600	5	600
P1C1C041	1	10	600	50	600	14	600	5	600
P1C1C052	1	10	600	50	600	14	600	5	600
P1C1C062	1	10	600	50	600	14	600	5	600
P1C1C077	1	10	600	50	600	14	600	5	600
P1C1C099	1	10	600	50	600	14	600	5	600
P1C1C125	1	10	600	50	600	14	600	5	600
P1C1C144	1	10	600	50	600	14	600	5	600
P1C1C192	1	10	600	25	600	18	600	SEE TABLE 4	
P1C1C242	1	10	600	25	600	18	600		
P1C1D002	1	10	208	65	208	25	208	5	208
P1C1D003	1	10	208	65	208	25	208	5	208
P1C1D004	1	10	208	65	208	25	208	5	208
P1C1D006	1	10	208	65	208	25	208	5	208
P1C1D007	1	10	208	65	208	25	208	5	208
P1C1D010	1	10	208	65	208	25	208	5	208
P1C1D016	1	10	208	65	208	25	208	5	208
P1C1D024	1	10	208	65	208	25	208	5	208
P1C1D030	1	10	208	65	208	25	208	5	208
P1C1D046	1	10	208	65	208	25	208	5	208
P1C1D059	1	10	208	65	208	25	208	5	208
P1C1D074	1	10	208	65	208	25	208	5	208
P1C1D088	1	10	208	65	208	25	208	5	208
P1C1D114	1	10	208	65	208	25	208	5	208
P1C1D143	1	10	208	65	208	25	208	5	208
P1C1D169	1	10	208	65	208	25	208	5	208
P1C1D211	1	10	208	65	208	65	208	SEE TABLE 4	
P1C1D273	1	10	208	65	208	65	208		
P1C1D343	1	10	208	65	208	65	208		
P1C1D396	1	10	208	65	208	65	208		

TABLE 4

WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083-SCCR_	WITH OPTION PD			
		①	②	③	④
P1C1C192	5	18	600	18	400
P1C1C242	5	18	600	18	400
P1C1D211	5	65	208	65	250
P1C1D273	5	65	208	65	400
P1C1D343	5	65	208	65	600
P1C1D396	5	65	208	65	600



 <p>THIS DOCUMENT AND INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF YASKAWA AMERICA INC.</p>	DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
	CHECKED: D.R. CMELAK	DATE: 8/23/12			
	TECH:	DATE:			
	APPROVED: K. FLIERL	DATE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 3 of 7
	ORIGINAL DESIGN: D.R. CMELAK	DATE: 3/19/12	DRAWING #: UDA00744		

TABLE 5

		WITHOUT OPTIONS PC,PD OR PE		WITH OPTION PC		WITH OPTION PE		WITH OPTION PD	
WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083- SCCR_	①	②	①	②	①	②	①	②
P1C2A002	1	10	240	65	240	25	240	5	240
P1C2A003	1	10	240	65	240	25	240	5	240
P1C2A004	1	10	240	65	240	25	240	5	240
P1C2A006	1	10	240	65	240	25	240	5	240
P1C2A009	1	10	240	65	240	25	240	5	240
P1C2A015	1	10	240	65	240	25	240	5	240
P1C2A022	1	10	240	65	240	25	240	5	240
P1C2A028	1	10	240	65	240	25	240	5	240
P1C2A042	1	10	240	65	240	25	240	5	240
P1C2A054	1	10	240	65	240	25	240	5	240
P1C2A068	1	10	240	65	240	25	240	5	240
P1C2A080	1	10	240	65	240	25	240	5	240
P1C2A104	1	10	240	65	240	25	240	5	240
P1C2A130	1	10	240	65	240	25	240	5	240
P1C2A154	1	10	240	65	240	25	240	5	240
P1C2A192	1	10	240	65	240	65	240	SEE TABLE 6	
P1C2A248	1	10	240	65	240	65	240		
P1C2A312	1	10	240	65	240	65	240		
P1C2A360	1	10	240	65	240	65	240		
P1C2B001	1	10	480	65	480	18	480	5	480
P1C2B002	1	10	480	65	480	18	480	5	480
P1C2B003	1	10	480	65	480	18	480	5	480
P1C2B004	1	10	480	65	480	18	480	5	480
P1C2B007	1	10	480	65	480	18	480	5	480
P1C2B011	1	10	480	65	480	18	480	5	480
P1C2B014	1	10	480	65	480	18	480	5	480
P1C2B021	1	10	480	65	480	18	480	5	480
P1C2B027	1	10	480	65	480	18	480	5	480
P1C2B034	1	10	480	65	480	18	480	5	480
P1C2B040	1	10	480	65	480	18	480	5	480
P1C2B052	1	10	480	65	480	18	480	5	480
P1C2B065	1	10	480	65	480	18	480	5	480
P1C2B077	1	10	480	65	480	18	480	5	480
P1C2B096	1	10	480	65	480	18	480	5	480
P1C2B124	1	10	480	65	480	18	480	5	480
P1C2B156	1	10	480	65	480	18	480	5	480
P1C2B180	1	10	480	65	480	35	480	SEE TABLE 6	
P1C2B240	1	10	480	65	480	35	480		
P1C2B302	1	10	480	65	480	35	480		
P1C2B361	1	10	480	65	480	35	480		
P1C2B414	1	10	480	65	480	35	480		
P1C2B477	1	10	480	65	480	35	480		
P1C2B515	1	10	480	65	480	35	480		
P1C2B590	1	10	480	65	480	35	480		
P1C2B660	1	10	480	65	480	35	480		
P1C2B720	1	10	480	65	480	35	480		
P1C2B810	1	10	480	65	480	35	480		
P1C2B900	1	10	480	65	480	35	480		
P1C2B930	1	10	480	65	480	35	480		
P1C2BK09	1	10	480	65	480	35	480		
P1C2BK20	1	10	480	65	480	35	480		

TABLE 6

		WITH OPTION PD			
WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083- SCCR_	①	②	③	④
P1C2A192	5	65	240	65	250
P1C2A248	5	65	240	65	400
P1C2A312	5	65	240	65	400
P1C2A360	5	65	240	65	600
P1C2B180	5	35	480	35	250
P1C2B240	5	35	480	35	400
P1C2B302	5	35	480	35	400
P1C2B361	5	35	480	35	400
P1C2B414	5	35	480	35	600
P1C2B477	5	65	480	65	600
P1C2B515	5	65	480	65	600
P1C2B590	5	65	480	65	800
P1C2B660	5	65	480	65	800
P1C2B720	5	65	480	65	1200
P1C2B810	5	65	480	65	1200
P1C2B900	5	65	480	65	1200
P1C2B930	5	65	480	65	1200
P1C2BK09	5	65	480	65	1200
P1C2BK20	5	65	480	65	1600



THIS DOCUMENT AND INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF YASKAWA AMERICA INC.

DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
CHECKED: D.R. CMELAK	DATE: 8/23/12			
TECH:	DATE:			
APPROVED: K. FLIERL	D16TE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 4 of 7
ORIGINAL DESIGN: D.R. CMELAK	DATE: 3/19/12	DRAWING #: UDA00744		

TABLE 7

WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083-SCCR_	WITHOUT OPTIONS PC,PD OR PE		WITH OPTION PC		WITH OPTION PE		WITH OPTION PD	
		①	②	①	②	①	②	①	②
P1C2C1P3	1	10	600	50	600	14	600	5	600
P1C2C1P7	1	10	600	50	600	14	600	5	600
P1C2C002	1	10	600	50	600	14	600	5	600
P1C2C003	1	10	600	50	600	14	600	5	600
P1C2C006	1	10	600	50	600	14	600	5	600
P1C2C009	1	10	600	50	600	14	600	5	600
P1C2C011	1	10	600	50	600	14	600	5	600
P1C2C017	1	10	600	50	600	14	600	5	600
P1C2C022	1	10	600	50	600	14	600	5	600
P1C2C027	1	10	600	50	600	14	600	5	600
P1C2C032	1	10	600	50	600	14	600	5	600
P1C2C041	1	10	600	50	600	14	600	5	600
P1C2C052	1	10	600	50	600	14	600	5	600
P1C2C062	1	10	600	50	600	14	600	5	600
P1C2C077	1	10	600	50	600	14	600	5	600
P1C2C099	1	10	600	50	600	14	600	5	600
P1C2C125	1	10	600	50	600	14	600	5	600
P1C2C144	1	10	600	50	600	14	600	5	600
P1C2C192	1	10	600	25	600	18	600	SEE TABLE 8	
P1C1C242	1	10	600	25	600	18	600		
P1C2D002	1	10	208	65	208	25	208	5	208
P1C2D003	1	10	208	65	208	25	208	5	208
P1C2D004	1	10	208	65	208	25	208	5	208
P1C2D006	1	10	208	65	208	25	208	5	208
P1C2D007	1	10	208	65	208	25	208	5	208
P1C2D010	1	10	208	65	208	25	208	5	208
P1C2D016	1	10	208	65	208	25	208	5	208
P1C2D024	1	10	208	65	208	25	208	5	208
P1C2D030	1	10	208	65	208	25	208	5	208
P1C2D046	1	10	208	65	208	25	208	5	208
P1C2D059	1	10	208	65	208	25	208	5	208
P1C2D074	1	10	208	65	208	25	208	5	208
P1C2D088	1	10	208	65	208	25	208	5	208
P1C2D114	1	10	208	65	208	25	208	5	208
P1C2D143	1	10	208	65	208	25	208	5	208
P1C2D169	1	10	208	65	208	25	208	5	208
P1C2D211	1	10	208	65	208	65	208	SEE TABLE 8	
P1C2D273	1	10	208	65	208	65	208		
P1C2D343	1	10	208	65	208	65	208		
P1C2D396	1	10	208	65	208	65	208		

TABLE 8

WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083-SCCR_	WITH OPTION PD			
		①	②	③	④
P1C2C192	5	18	600	18	400
P1C1C242	5	18	600	18	400
P1C2D211	5	65	208	65	250
P1C2D273	5	65	208	65	400
P1C2D343	5	65	208	65	600
P1C2D396	5	65	208	65	600


 <p>THIS DOCUMENT AND INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF YASKAWA AMERICA INC.</p>	DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
	CHECKED: D.R. CMELAK	DATE: 8/23/12			
	TECH:	DATE:			
	APPROVED: K. FLIERL	DATE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 5 of 7
ORIGINAL DESIGN: D.R. CMELAK	DATE: 3/19/12	DRAWING #: UDA00744			

TABLE 9

		WITHOUT OPTIONS PC,PD OR PE		WITH OPTION PC		WITH OPTION PE		WITH OPTION PD	
WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083- SCCR_	①	②	①	②	①	②	①	②
P1C3A002	1	10	240	65	240	25	240	5	240
P1C3A003	1	10	240	65	240	25	240	5	240
P1C3A004	1	10	240	65	240	25	240	5	240
P1C3A006	1	10	240	65	240	25	240	5	240
P1C3A009	1	10	240	65	240	25	240	5	240
P1C3A015	1	10	240	65	240	25	240	5	240
P1C3A022	1	10	240	65	240	25	240	5	240
P1C3A028	1	10	240	65	240	25	240	5	240
P1C3A042	1	10	240	65	240	25	240	5	240
P1C3A054	1	10	240	65	240	25	240	5	240
P1C3A068	1	10	240	65	240	25	240	5	240
P1C3A080	1	10	240	65	240	25	240	5	240
P1C3A104	1	10	240	65	240	25	240	5	240
P1C3A130	1	10	240	65	240	25	240	5	240
P1C3A154	1	10	240	65	240	25	240	5	240
P1C3A192	1	10	240	65	240	65	240	SEE TABLE 10	
P1C3A248	1	10	240	65	240	65	240		
P1C3A312	1	10	240	65	240	65	240		
P1C3A360	1	10	240	65	240	65	240		
P1C3B001	1	10	480	65	480	18	480	5	480
P1C3B002	1	10	480	65	480	18	480	5	480
P1C3B003	1	10	480	65	480	18	480	5	480
P1C3B004	1	10	480	65	480	18	480	5	480
P1C3B007	1	10	480	65	480	18	480	5	480
P1C3B011	1	10	480	65	480	18	480	5	480
P1C3B014	1	10	480	65	480	18	480	5	480
P1C3B021	1	10	480	65	480	18	480	5	480
P1C3B027	1	10	480	65	480	18	480	5	480
P1C3B034	1	10	480	65	480	18	480	5	480
P1C3B040	1	10	480	65	480	18	480	5	480
P1C3B052	1	10	480	65	480	18	480	5	480
P1C3B065	1	10	480	65	480	18	480	5	480
P1C3B077	1	10	480	65	480	18	480	5	480
P1C3B096	1	10	480	65	480	18	480	5	480
P1C3B124	1	10	480	65	480	18	480	5	480
P1C3B156	1	10	480	65	480	18	480	5	480
P1C3B180	1	10	480	65	480	35	480	SEE TABLE 10	
P1C3B240	1	10	480	65	480	35	480		
P1C3B302	1	10	480	65	480	35	480		
P1C3B361	1	10	480	65	480	35	480		
P1C3B414	1	10	480	65	480	35	480		
P1C3B477	1	10	480	65	480	35	480		
P1C3B515	1	10	480	65	480	35	480		
P1C3B590	1	10	480	65	480	35	480		
P1C3B660	1	10	480	65	480	35	480		
P1C3B720	1	10	480	65	480	35	480		
P1C3B810	1	10	480	65	480	35	480		
P1C3B900	1	10	480	65	480	35	480		
P1C3B930	1	10	480	65	480	35	480		
P1C3BK09	1	10	480	65	480	35	480		
P1C3BK20	1	10	480	65	480	35	480		

TABLE 10

		WITH OPTION PD			
WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083- SCCR_	①	②	③	④
P1C3A192	5	65	240	65	250
P1C3A248	5	65	240	65	400
P1C3A312	5	65	240	65	400
P1C3A360	5	65	240	65	600
P1C3B180	5	35	480	35	250
P1C3B240	5	35	480	35	400
P1C3B302	5	35	480	35	400
P1C3B361	5	35	480	35	400
P1C3B414	5	35	480	35	600
P1C3B477	5	65	480	65	600
P1C3B515	5	65	480	65	600
P1C3B590	5	65	480	65	800
P1C3B660	5	65	480	65	800
P1C3B720	5	65	480	65	1200
P1C3B810	5	65	480	65	1200
P1C3B900	5	65	480	65	1200
P1C3B930	5	65	480	65	1200
P1C3BK09	5	65	480	65	1600
P1C3BK20	5	65	480	65	1600

YASKAWA
 THIS DOCUMENT AND INFORMATION
 CONTAINED IN IT ARE CONFIDENTIAL,
 AND CANNOT BE COPIED OR
 DISCLOSED IN WHOLE OR IN PART
 WITHOUT THE EXPRESS WRITTEN
 CONSENT OF YASKAWA AMERICA INC.


DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
CHECKED: D.R. CMELAK	DATE: 8/23/12			
TECH:	DATE:			
APPROVED: K. FLIERL	DATE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 6 of 7
ORIGINAL DESIGN: D.R. CMELAK	DATE: 3/19/12	DRAWING #: UDA00744		

TABLE 11

WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083-SCCR_	WITHOUT OPTIONS PC,PD OR PE		WITH OPTION PC		WITH OPTION PE		WITH OPTION PD	
		①	②	①	②	①	②	①	②
P1C3C1P3	1	10	600	50	600	14	600	5	600
P1C3C1P7	1	10	600	50	600	14	600	5	600
P1C3C002	1	10	600	50	600	14	600	5	600
P1C3C003	1	10	600	50	600	14	600	5	600
P1C3C006	1	10	600	50	600	14	600	5	600
P1C3C009	1	10	600	50	600	14	600	5	600
P1C3C011	1	10	600	50	600	14	600	5	600
P1C3C017	1	10	600	50	600	14	600	5	600
P1C3C022	1	10	600	50	600	14	600	5	600
P1C3C027	1	10	600	50	600	14	600	5	600
P1C3C032	1	10	600	50	600	14	600	5	600
P1C3C041	1	10	600	50	600	14	600	5	600
P1C3C052	1	10	600	50	600	14	600	5	600
P1C3C062	1	10	600	50	600	14	600	5	600
P1C3C077	1	10	600	50	600	14	600	5	600
P1C3C099	1	10	600	50	600	14	600	5	600
P1C3C125	1	10	600	50	600	14	600	5	600
P1C3C144	1	10	600	50	600	14	600	5	600
P1C3C192	1	10	600	25	600	18	600	SEE TABLE 12	
P1C3C242	1	10	600	25	600	18	600		
P1C3D002	1	10	208	65	208	25	208	5	208
P1C3D003	1	10	208	65	208	25	208	5	208
P1C3D004	1	10	208	65	208	25	208	5	208
P1C3D006	1	10	208	65	208	25	208	5	208
P1C3D007	1	10	208	65	208	25	208	5	208
P1C3D010	1	10	208	65	208	25	208	5	208
P1C3D016	1	10	208	65	208	25	208	5	208
P1C3D024	1	10	208	65	208	25	208	5	208
P1C3D030	1	10	208	65	208	25	208	5	208
P1C3D046	1	10	208	65	208	25	208	5	208
P1C3D059	1	10	208	65	208	25	208	5	208
P1C3D074	1	10	208	65	208	25	208	5	208
P1C3D088	1	10	208	65	208	25	208	5	208
P1C3D114	1	10	208	65	208	25	208	5	208
P1C3D143	1	10	208	65	208	25	208	5	208
P1C3D169	1	10	208	65	208	25	208	5	208
P1C3D211	1	10	208	65	208	65	208	SEE TABLE 12	
P1C3D273	1	10	208	65	208	65	208		
P1C3D343	1	10	208	65	208	65	208		
P1C3D396	1	10	208	65	208	65	208		

TABLE 12

WORK ORDER PART NO. BEGINNING	USE FORMAT UNPN0083-SCCR_	WITH OPTION PD			
		①	②	③	④
P1C3C192	5	18	600	18	400
P1C3C242	5	18	600	18	400
P1C3D211	5	65	208	65	250
P1C3D273	5	65	208	65	400
P1C3D343	5	65	208	65	600
P1C3D396	5	65	208	65	600

 <p>THIS DOCUMENT AND INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF YASKAWA AMERICA INC.</p>	DRAWN BY: K. MALUSIC	DATE: 8/23/12	TITLE: AC DRIVE DATA NAMEPLATE SHORT CIRCUIT RATING DATA FORMAT FOR P1000		
	CHECKED: D.R. CMELAK	DATE: 8/23/12			
	TECH:	DATE:			
	APPROVED: K. FLIERL	DATE: 8/23/12	SIZE: C	REVISION: 02	PAGE: 7 of 7
ORIGINAL DESIGN: D.R. CMELAK	DATE: 3/19/12	DRAWING #: UDA00744			